

A L E Y



60x120 R
23³/₄"x47¹/₄" R



100x100 R
40"x40" R

Aley

PORCELÁNICO ESMALTADO / GLAZED PORCELAIN TILE
ACABADO PULIDO / POLISHED FINISH

LUX

23³/₄"x47¹/₄" R 60x120 R



Aley Cream Pul 60x120 R



Aley White Pul 60x120 R

P460R



Aley Cream Pul 60x120 R

P460R

Aley

PORCELÁNICO ESMALTADO / GLAZED PORCELAIN TILE
ACABADO PULIDO / POLISHED FINISH

LUX

40"x40" R 100x100 R



Aley Cream Pul 100x100 R



Aley White Pul 100x100 R

P410R



Aley Cream Pul 100x100 R

P410R

Aley

PASTA PORCELÁNICA / PORCELAIN CLAY
ACABADO SATINADO / SATIN FINISH

23³/₄"x47¹/₄" R 60x120 R



Aley White Sat 60x120 R



Aley White Sat 60x120 R

G461R



Aley Cream Sat 60x120 R

G461R

Aley

PASTA PORCELÁNICA / PORCELAIN CLAY
ACABADO SATINADO / SATIN FINISH

Aley White Sat 100x100 R

40"x40" R 100x100 R



Aley White Sat 100x100 R

G413R



Aley Cream Sat 100x100 R

G413R

Technical Characteristics

Características técnicas

DESCRIPCIÓN DEL TEST TEST DESCRIPTION		NORMA STANDARD	GRUPO B1a Porcelánico esmaltado Glazed Porcelain Tile	GRUPO B1b Pasta porcelánica Porcelain Clay
Absorción de agua / Water absorption		UNE-EN ISO 10545-3	Ev ≤ 0,5%	0,5% < Ev ≤ 3%
Fuerza de rotura / Breaking Strength		UNE-EN ISO 10545-4	≥ 1300 N	≥ 1100 N
Resistencia a la flexión / Modulus of rupture		UNE-EN ISO 10545-4	≥ 35 N/mm ²	≥ 30 N/mm ²
Abrasion superficial / Surface Abrasion		UNE-EN-ISO 10545-7	A consultar según modelo Consult according to model	A consultar según modelo Consult according to model
Resistencia al cuarteo / Crazeing resistance		UNE-EN ISO 10545-11	Requerido / Requested	Requerido / Requested
Resistencia a la helada / Frost resistance		UNE-EN ISO 10545-12	Requerido / Requested	Requerido / Requested
Resistencia química Chemical resistance	Productos domésticos y de piscina Household chemicals and swimming pool salts	UNE-EN ISO 10545-13	Mínimo clase B Minimum class B	Mínimo clase B Minimum class B
	Ácidos a baja concentración Low concentration of acids	UNE-EN ISO 10545-13	Mínimo clase LB Minimum class LB	Mínimo clase LB Minimum class LB
	Bases a baja concentración Low concentration of alkalis	UNE-EN ISO 10545-13	Mínimo clase LB Minimum class LB	Mínimo clase LB Minimum class LB
Resistencia a las manchas / Stain resistance		UNE-EN ISO 10545-14	Mínimo clase 3 Minimum Class 3	Mínimo clase 3 Minimum Class 3

Symbology

Características técnicas



NOVEDAD
NEW SERIES



PORCELÁNICO ESMALTADO
GLAZED PORCELAIN TILES



PULIDO
POLISHED



RECTIFICADO
RECTIFIED



MÁRMOL
MARBLE



ANTIHELO
ANTIFREEZE



LIGERA VARIACIÓN
LIGHT VARIATION



PASTA PORCELÁNICA
PORCELAIN CLAY



SATINADO
SATIN



DIFERENTES GRÁFICAS
DIFFERENT GRAPHICS

Packing List

PORCELÁNICO ESMALTADO / GLAZED PORCELAIN TILE									
Formato Nominal Nominal Size	Formato de trabajo Work size	Pzas/Cj	m ² /Cj	Kg/Cj	Kg/m ²	Pzs/Epl	Cjas/Epl	m ² /Epl	Kg/Epl
60x120 R PUL	59x119 R	2	1,4042	33,06	23,54	72	36	50,55	1.215,00
100x100 R PUL	98x98 R	2	1,9208	46,48	24,20	40	20	38,42	950,00
60x120 R	59,5x120 R	2	1,4280	30,38	21,27	80	40	57,12	1.240,00
100x100 R	99,5x99,5 R	2	1,9801	43,33	21,88	48	24	47,52	1.060,00

© Copyright KTL, S.L.U.

Reservados todos los derechos.

KTL se reserva el derecho de modificar las características de sus productos sin preaviso de ningún tipo.

Los acabados se dan a título indicativo, quedando bajo reserva los ajustes de los colores consecuencia de las técnicas de impresión. Por ello las fotografías de los productos expuestos no son contractuales.

All rights reserved.

KTL reserves the right to change the characteristics of its products without prior notice.

Information about the finishes of the goods is only provided as a guide. As a result of the printing techniques there might be differences between the colours printed in this catalogue and these of the real products. Colours shown in this catalogue are not contractual.

KTLC
CERÁMICA

Partida Casablanca nº 6 / 12593 Moncofar, Castellón. Spain

Phone: +34 964 584 069 / e-mail: info@ktlceramica.com / web: www.ktlceramica.com